

# Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 18

SDS No.: 152782

V002.0 Revision: 19.07.2019

printing date: 03.04.2021

Replaces version from: 16.10.2018

LOCTITE SI 5145 known as NUVA-SIL(R) 5145

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE SI 5145 known as NUVA-SIL(R) 5145

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Silicone sealant

### 1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0 Fax-no.: +49 211 798 2009

ua-productsafety.de@henkel.com

## 1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

## **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

### 2.2. Label elements

## Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

**Supplemental information** EUH210 Safety data sheet available on request.

### 2.3. Other hazards

Methoxy curing silicones release methanol in contact with moisture. Methanol is toxic if swallowed and harmful by inhalation. It is highly flammable.

This product contains trace quantities of Hexamethyldisilazane. Hexamethyldisilazane reacts instantly with residual moisture in the package, and produces correspondingly small amounts of ammonia.

This mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

### General chemical description:

Silicone sealant

### Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Silane, dimethoxydimethyl- 1112-39-6	214-189-4 01-2119976290-35	1-< 5 %	Flam. Liq. 2 H225
Tetraethyl silicate 78-10-4	201-083-8 01-2119496195-28	1-< 5 %	Flam. Liq. 3 H226 Acute Tox. 4; Inhalation H332 Eye Irrit. 2 H319 STOT SE 3 H335
Octamethylcyclotetrasiloxane 556-67-2	209-136-7 01-2119529238-36	0,1-< 1 %	Flam. Liq. 3 H226 Repr. 2 H361f Aquatic Chronic 4 H413 ===== EU. REACH Candidate List of Substances of Very High Concern for Authorization (SVHC)
Hexamethyldisilizane 999-97-3	213-668-5 01-2119438176-38	0,1-< 1 %	Flam. Liq. 2 H225 Acute Tox. 4; Oral H302 Acute Tox. 3; Dermal H311 Acute Tox. 4; Inhalation H332 Aquatic Chronic 3 H412
Decamethylcyclopentasiloxane 541-02-6	208-764-9 01-2119511367-43	0,1-< 1 %	Aquatic Chronic 4  H413 =====  EU. REACH Candidate List of Substances of Very High Concern for Authorization (SVHC)
Dodecamethylcyclohexasiloxane 540-97-6	208-762-8 01-2119517435-42	0,1-< 1 %	Aquatic Chronic 4  H413 =====  EU. REACH Candidate List of Substances of Very High Concern for Authorization (SVHC)

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

# **SECTION 4: First aid measures**

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Prolonged or repeated contact may cause skin irritation.

Prolonged or repeated contact may cause eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

### Suitable extinguishing media:

Carbon dioxide, foam, powder

### Extinguishing media which must not be used for safety reasons:

None known

## 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released. Silicon dioxide

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus.

### Additional information:

In case of fire, keep containers cool with water spray.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Ensure adequate ventilation.

Wear protective equipment.

### **6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

### 6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

### 6.4. Reference to other sections

See advice in section 8

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Use only in well-ventilated areas. Vapours should be extracted to avoid inhalation. Avoid skin and eye contact. See advice in section 8

### Hygiene measures:

Good industrial hygiene practices should be observed. Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, well-ventilated place. Refer to Technical Data Sheet Never allow product to get in contact with water during storage

### 7.3. Specific end use(s)

Silicone sealant

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### **Occupational Exposure Limits**

Valid for

Germany

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Tetraethyl orthosilicate 78-10-4 [TETRAETHYL ORTHOSILICATE]	5	44	Time Weighted Average (TWA):	Indicative	ECTLV
Tetraethyl orthosilicate 78-10-4	1,4	12	Exposure limit(s):	1	TRGS 900
Tetraethyl orthosilicate 78-10-4			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900

# $\label{eq:predicted} \textbf{Predicted No-Effect Concentration (PNEC):}$

Name on list	Environmental Compartment	Exposure period	Value			Remarks	
	P. C.	F	mg/l	ppm	mg/kg	others	
Tetraethyl silicate	aqua		0,192 mg/l				
78-10-4 Tetraethyl silicate	(freshwater) aqua (marine		0,0192				
78-10-4	water)		0,0192 mg/l				
Tetraethyl silicate	aqua		10 mg/l				
78-10-4	(intermittent releases)						
Tetraethyl silicate	sediment				0,83 mg/kg		
78-10-4	(freshwater)				0.092		
Tetraethyl silicate 78-10-4	(marine water)				0,083 mg/kg		
Tetraethyl silicate	Soil				0,05 mg/kg		
78-10-4							
Tetraethyl silicate 78-10-4	sewage treatment plant		4000 mg/l				
70-10-4	(STP)						
Octamethylcyclotetrasiloxane	aqua		0,0015				
556-67-2	(freshwater)		mg/l				
Octamethylcyclotetrasiloxane 556-67-2	aqua (marine water)		0,00015 mg/l				
Octamethylcyclotetrasiloxane	sewage		10 mg/l				
556-67-2	treatment plant						
Octamethylcyclotetrasiloxane	(STP) sediment				3 mg/kg		
556-67-2	(freshwater)				J mg/kg		
Octamethylcyclotetrasiloxane	sediment				0,3 mg/kg		
556-67-2 Octamethylcyclotetrasiloxane	(marine water) oral				41 mg/kg		
556-67-2							
Octamethylcyclotetrasiloxane 556-67-2	Soil				0,54 mg/kg		
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	aqua (freshwater)		0,25 mg/l				
1,1,1,3,3,3-Hexamethyldisilazane	aqua (marine		0,025 mg/l				
999-97-3	water)						
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	sediment (freshwater)				0,45 mg/kg		
1,1,1,3,3,3-Hexamethyldisilazane	sediment				0,045		
999-97-3	(marine water)				mg/kg		
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	Soil				0,22 mg/kg		
1,1,1,3,3,3-Hexamethyldisilazane	sewage		67 mg/l				
999-97-3	treatment plant (STP)						
Decamethylcyclopentasiloxane	aqua		0,0012				
541-02-6	(freshwater)		mg/l				
Decamethylcyclopentasiloxane 541-02-6	aqua (marine water)		0,00012				
Decamethylcyclopentasiloxane	sewage		mg/l 10 mg/l				
541-02-6	treatment plant (STP)		l o mg/1				
Decamethylcyclopentasiloxane 541-02-6	sediment				11 mg/kg		
Decamethylcyclopentasiloxane	(freshwater) Soil				1,27 mg/kg		
541-02-6 Decamethylcyclopentasiloxane	oral			1	16 mg/kg	1	
541-02-6					10 1116/116		
Decamethylcyclopentasiloxane 541-02-6	sediment (marine water)				1,1 mg/kg		
Dodecamethylcyclohexasiloxane	sediment				2,826		
540-97-6	(freshwater)				mg/kg		
Dodecamethylcyclohexasiloxane 540-97-6	sediment				0,282		
Dodecamethylcyclohexasiloxane	(marine water) Soil				mg/kg 3,336		
540-97-6					mg/kg		
Dodecamethylcyclohexasiloxane	sewage	-	1 mg/l				
540-97-6	treatment plant (STP)						

# **Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Tetraethyl silicate 78-10-4	Workers	dermal	Acute/short term exposure - systemic effects		56 mg/kg	
Tetraethyl silicate 78-10-4	Workers	Inhalation	Acute/short term exposure - systemic effects		85 mg/m3	
Tetraethyl silicate 78-10-4	Workers	Inhalation	Acute/short term exposure - local effects		85 mg/m3	
Tetraethyl silicate 78-10-4	Workers	dermal	Long term exposure - systemic effects		56 mg/kg	
Tetraethyl silicate 78-10-4	Workers	Inhalation	Long term exposure - systemic effects		85 mg/m3	
Tetraethyl silicate 78-10-4	Workers	Inhalation	Long term exposure - local effects		85 mg/m3	
Tetraethyl silicate 78-10-4	General population	dermal	Acute/short term exposure - systemic effects		3 mg/kg	
Tetraethyl silicate 78-10-4	General population	Inhalation	Acute/short term exposure - local effects		14 mg/m3	
Tetraethyl silicate 78-10-4	General population	Inhalation	Acute/short term exposure - systemic effects		14 mg/m3	
Tetraethyl silicate 78-10-4	General population	dermal	Long term exposure - systemic effects		3 mg/kg	
Tetraethyl silicate 78-10-4	General population	Inhalation	Long term exposure - systemic effects		14 mg/m3	
Tetraethyl silicate 78-10-4	General population	Inhalation	Long term exposure - local effects		14 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	Workers	inhalation	Long term exposure - systemic effects		73 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	Workers	inhalation	Long term exposure - local effects		73 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	Workers	inhalation	Acute/short term exposure - systemic effects		73 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	Workers	inhalation	Acute/short term exposure - local effects		73 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	inhalation	Long term exposure - systemic effects		13 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	inhalation	Long term exposure - local effects		13 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	inhalation	Acute/short term exposure - systemic effects		13 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	inhalation	Acute/short term exposure - local effects		13 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	oral	Long term exposure - systemic effects		3,7 mg/kg	
Octamethylcyclotetrasiloxane 556-67-2	General population	oral	Acute/short term exposure - systemic effects		3,7 mg/kg	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	Workers	inhalation	Long term exposure - systemic effects		53 mg/m3	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	Workers	inhalation	Acute/short term exposure -		53 mg/m3	

I	ĺ	İ	systemic effects	i i	i
1,1,1,3,3,3-Hexamethyldisilazane	Workers	inhalation	Long term	133 mg/m3	
999-97-3	Workers	iiiiaiatioii	exposure - local	133 mg m3	
			effects		
1,1,1,3,3,3-Hexamethyldisilazane	Workers	inhalation	Acute/short term	133 mg/m3	
999-97-3			exposure - local		
		4	effects		
1,1,1,3,3,3-Hexamethyldisilazane	Workers	dermal	Long term	7,5 mg/kg	
999-97-3			exposure -		
1 1 1 2 2 2 Hayamathyildisilagana	Workers	dermal	systemic effects Acute/short term	7.5 mg/lrg	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	Workers	dermai	exposure -	7,5 mg/kg	
			systemic effects		
1,1,1,3,3,3-Hexamethyldisilazane	General	inhalation	Long term	3,7 mg/m3	
999-97-3	population		exposure -	s, mg me	
	1 1		systemic effects		
1,1,1,3,3,3-Hexamethyldisilazane	General	inhalation	Acute/short term	3,7 mg/m3	
999-97-3	population		exposure -		
			systemic effects		
1,1,1,3,3,3-Hexamethyldisilazane	General	inhalation	Long term	1,7 mg/m3	
999-97-3	population		exposure - local		
1112221 4 11 1	C 1		effects Acute/short term	1.7 / 2	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	General	inhalation	Acute/snort term exposure - local	1,7 mg/m3	
999-97-3	population		effects		
1,1,1,3,3,3-Hexamethyldisilazane	General	oral	Long term	1,1 mg/kg	
999-97-3	population	Orai	exposure -	1,1 mg/kg	
	Population		systemic effects		
1,1,1,3,3,3-Hexamethyldisilazane	General	oral	Acute/short term	1,1 mg/kg	
999-97-3	population		exposure -	1,7 18, 18	
	1 1		systemic effects		
Decamethylcyclopentasiloxane	Workers	inhalation	Acute/short term	97,3 mg/m3	
541-02-6			exposure -		
			systemic effects		
Decamethylcyclopentasiloxane	Workers	inhalation	Acute/short term	24,2 mg/m3	
541-02-6			exposure - local		
D 41 1 4 7	337 1		effects	07.2	
Decamethylcyclopentasiloxane	Workers	inhalation	Long term	97,3 mg/m3	
541-02-6			exposure - systemic effects		
Decamethylcyclopentasiloxane	Workers	inhalation	Long term	24,2 mg/m3	
541-02-6	WOIKEIS	Illiaiation	exposure - local	24,2 mg/m3	
341-02-0			effects		
Decamethylcyclopentasiloxane	General	inhalation	Acute/short term	17,3 mg/m3	
541-02-6	population		exposure -	17,5 mg ms	
	1 1		systemic effects		
Decamethylcyclopentasiloxane	General	inhalation	Acute/short term	4,3 mg/m3	
541-02-6	population		exposure - local		
			effects		
Decamethylcyclopentasiloxane	General	oral	Long term	5 mg/kg	
541-02-6	population		exposure -		
	G 1		systemic effects	150 / 0	
Decamethylcyclopentasiloxane 541-02-6	General	inhalation	Long term exposure -	17,3 mg/m3	
341-02-0	population		systemic effects		
Decamethylcyclopentasiloxane	General	inhalation	Long term	4,3 mg/m3	
541-02-6	population	iiiiaiatioii	exposure - local	4,5 mg/m3	
341 02 0	population		effects		
Decamethylcyclopentasiloxane	General	oral	Acute/short term	5 mg/kg	
541-02-6	population	5141	exposure -		
	r · r · · · ·		systemic effects		
Dodecamethylcyclohexasiloxane	Workers	inhalation	Long term	11 mg/m3	
540-97-6			exposure -		
			systemic effects		
Dodecamethylcyclohexasiloxane	Workers	inhalation	Long term	1,22 mg/m3	
540-97-6			exposure - local		
	***	1	effects		
Dodecamethylcyclohexasiloxane	Workers	inhalation	Acute/short term	6,1 mg/m3	
540-97-6		1	exposure - local		
Dodgoomathylayalahayas!!	Company 1	inholati	effects Long torm	2.7 m a/m2	
Dodecamethylcyclohexasiloxane 540-97-6	General population	inhalation	Long term exposure -	2,7 mg/m3	
J=0-21-0	population		systemic effects		
Dodecamethylcyclohexasiloxane	General	inhalation	Long term	0,3 mg/m3	
540-97-6	population	IIIIIaiaiioii	exposure - local	0,5 1115/1115	
	r spannion	1	effects		
i .					

Dodecamethylcyclohexasiloxane 540-97-6	General population	inhalation	Acute/short term exposure - local effects	1,5 mg/m3	
Dodecamethylcyclohexasiloxane 540-97-6	General population	oral	Long term exposure - systemic effects	1,7 mg/kg	
Dodecamethylcyclohexasiloxane 540-97-6	General population	oral	Acute/short term exposure - systemic effects	1,7 mg/kg	

#### **Biological Exposure Indices:**

None

#### 8.2. Exposure controls:

Engineering controls:

Ensure adequate ventilation.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

### Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq$  0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Appearance paste transparent Odor Alcoholic

Odour threshold No data available / Not applicable

pH No data available / Not applicable
Melting point No data available / Not applicable
Solidification temperature No data available / Not applicable

Initial boiling point

No data available / Not applicable
Flash point

Product is a solid. (ASTM D 4359)
Evaporation rate

No data available / Not applicable
Flammability

No data available / Not applicable
Explosive limits

No data available / Not applicable

Vapour pressure < 13 mbar (21 °C (69.8 °F))

Relative vapour density: No data available / Not applicable

Density 1,1 g/cm<sup>3</sup>

()
Bulk density
No data available / Not applicable
Solubility
No data available / Not applicable
Solubility (qualitative)
Polymerises in presence of water.

(Solvent: Water)
Solubility (qualitative)
Not determined

(Solvent: Acetone)

Partition coefficient: n-octanol/water
Auto-ignition temperature
Decomposition temperature
Viscosity
Viscosity
Viscosity
Viscosity
Viscosity
Viscosity
No data available / Not applicable
No data available / Not applicable
Viscosity
Viscosity
No data available / Not applicable
Explosive properties
No data available / Not applicable
Oxidising properties
No data available / Not applicable
No data available / Not applicable

#### 9.2. Other information

No data available / Not applicable

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Polymerises in presence of water.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

### 10.4. Conditions to avoid

No decomposition if used according to specifications. Exposure to air or moisture over prolonged periods.

### 10.5. Incompatible materials

See section reactivity.

### 10.6. Hazardous decomposition products

Methanol is liberated slowly upon exposure to moisture.

# **SECTION 11: Toxicological information**

## General toxicological information:

Prolonged or repeated contact may cause skin irritation.

Prolonged or repeated contact may cause eye irritation.

Methanol released during polymerisation of RTV silicones is toxic by inhalation. It is also highly flammable

### 11.1. Information on toxicological effects

## Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Silane, dimethoxydimethyl- 1112-39-6	LD50	> 2.007 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Tetraethyl silicate 78-10-4	LD50	> 2.500 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Octamethylcyclotetrasilox ane 556-67-2	LD50	> 4.800 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Hexamethyldisilizane 999-97-3	LD50	851 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Decamethylcyclopentasilo xane 541-02-6	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Dodecamethylcyclohexasi loxane 540-97-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)

### Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Octamethylcyclotetrasilox	LD50	> 2.375 mg/kg	rat	equivalent or similar to OECD Guideline 402 (Acute
ane				Dermal Toxicity)
556-67-2				
Hexamethyldisilizane	LD50	547 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
999-97-3				
Decamethylcyclopentasilo	LD50	> 2.000 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute
xane				Dermal Toxicity)
541-02-6				
Dodecamethylcyclohexasi	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
loxane				
540-97-6				

## Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Test atmosphere	Exposure	Species	Method
CAS-No.	type			time		
Octamethylcyclotetrasilox	LC50	36 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute
ane						Inhalation Toxicity)
556-67-2						
Hexamethyldisilizane	Acute	10,1 mg/l	vapour			Expert judgement
999-97-3	toxicity					
	estimate					
	(ATE)					
Decamethylcyclopentasilo	LC50	8,67 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute
xane						Inhalation Toxicity)
541-02-6						

### Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
Tetraethyl silicate	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
78-10-4				
Octamethylcyclotetrasilox	not irritating		rabbit	equivalent or similar to OECD Guideline 404 (Acute
ane				Dermal Irritation / Corrosion)
556-67-2				
Decamethylcyclopentasilo	not irritating	24 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute
xane				Dermal Irritation / Corrosion)
541-02-6				
Dodecamethylcyclohexasi	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
loxane				
540-97-6				

## Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
Octamethylcyclotetrasilox	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye
ane				Irritation / Corrosion)
556-67-2				
Decamethylcyclopentasilo	not irritating	24 h	rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye
xane				Irritation / Corrosion)
541-02-6				
Dodecamethylcyclohexasi	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
loxane				
540-97-6				

### Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Tetraethyl silicate 78-10-4	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Octamethylcyclotetrasilox ane 556-67-2	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Decamethylcyclopentasilo xane 541-02-6	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Dodecamethylcyclohexasi loxane 540-97-6	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

# Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Tetraethyl silicate 78-10-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
Octamethylcyclotetrasilox ane 556-67-2	negative	bacterial gene mutation assay	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Octamethylcyclotetrasilox ane 556-67-2	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Octamethylcyclotetrasilox ane 556-67-2	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Hexamethyldisilizane 999-97-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Hexamethyldisilizane 999-97-3	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Decamethylcyclopentasilo xane 541-02-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Decamethylcyclopentasilo xane 541-02-6	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Decamethylcyclopentasilo xane 541-02-6	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Dodecamethylcyclohexasi loxane 540-97-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Dodecamethylcyclohexasi loxane 540-97-6	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Octamethylcyclotetrasilox ane 556-67-2	negative	inhalation		rat	equivalent or similar to OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
Octamethylcyclotetrasilox ane 556-67-2	negative	oral: gavage		rat	equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)
Decamethylcyclopentasilo xane 541-02-6	negative	inhalation		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
Decamethylcyclopentasilo xane 541-02-6	negative	inhalation: vapour		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Dodecamethylcyclohexasi loxane 540-97-6	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

# Carcinogenicity

No data available.

# Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result / Value	Test type	Route of	Species	Method
CAS-No.			application	_	
Octamethylcyclotetrasilox	NOAEL P 300 ppm	two-	inhalation	rat	equivalent or similar to
ane		generation			OECD Guideline 416 (Two-
556-67-2	NOAEL F1 300 ppm	study			Generation Reproduction
					Toxicity Study)
Decamethylcyclopentasilo	NOAEL P >= 160 ppm	two-	inhalation:	rat	EPA OPPTS 870.3800
xane		generation	vapour		(Reproduction and Fertility
541-02-6	NOAEL F1 >= 160 ppm	study			Effects)
	NOAEL F2 >= 160 ppm				
Dodecamethylcyclohexasi	NOAEL P 1.000 mg/kg	screening	oral: gavage	rat	OECD Guideline 422
loxane					(Combined Repeated Dose
540-97-6	NOAEL F1 1.000 mg/kg				Toxicity Study with the
					Reproduction /
					Developmental Toxicity
				1	Screening Test)

## STOT-single exposure:

No data available.

# STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Octamethylcyclotetrasilox ane 556-67-2	LOAEL 35 ppm	inhalation	6 h nose only inhalation 5 days/week for 13 weeks	rat	OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day)
Octamethylcyclotetrasilox ane 556-67-2	NOAEL 960 mg/kg	dermal	3 w 5 d/w	rabbit	equivalent or similar to OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Decamethylcyclopentasilo xane 541-02-6	NOAEL >= 1.000 mg/kg	oral: gavage	13 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Dodecamethylcyclohexasi loxane 540-97-6	NOAEL 1.000 mg/kg	oral: gavage	29 d daily, 7 d/w	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

## Aspiration hazard:

No data available.

# **SECTION 12: Ecological information**

# General ecological information:

Do not empty into drains / surface water / ground water.

### 12.1. Toxicity

## **Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		_		
Tetraethyl silicate	LC50	> 245 mg/l	96 h	Brachydanio rerio (new name:	EU Method C.1 (Acute
78-10-4				Danio rerio)	Toxicity for Fish)
Octamethylcyclotetrasiloxane	NOEC	0,0044 mg/l	93 d	Salmo gairdneri (new name:	other guideline:
556-67-2				Oncorhynchus mykiss)	
Octamethylcyclotetrasiloxane	LC50		96 h	Oncorhynchus mykiss	EPA OTS 797.1400 (Fish
556-67-2					Acute Toxicity Test)
Hexamethyldisilizane	LC50	88 mg/l	96 h	Brachydanio rerio (new name:	OECD Guideline 203 (Fish,
999-97-3				Danio rerio)	Acute Toxicity Test)
Decamethylcyclopentasiloxan	LC50		96 h	Leuciscus idus	OECD Guideline 203 (Fish,
e					Acute Toxicity Test)
541-02-6					
Decamethylcyclopentasiloxan	NOEC		90 d	Oncorhynchus mykiss	OECD Guideline 210 (fish
e					early lite stage toxicity test)
541-02-6					

### Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Silane, dimethoxydimethyl-	EC50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202
1112-39-6					(Daphnia sp. Acute
					Immobilisation Test)
Tetraethyl silicate	EC50	> 75 mg/l	48 h	Daphnia magna	OECD Guideline 202
78-10-4					(Daphnia sp. Acute
					Immobilisation Test)
Octamethylcyclotetrasiloxane	EC50		48 h	Daphnia magna	EPA OTS 797.1300
556-67-2					(Aquatic Invertebrate Acute
					Toxicity Test, Freshwater
					Daphnids)
Hexamethyldisilizane	EC50	80 mg/l	48 h	Daphnia magna	OECD Guideline 202
999-97-3					(Daphnia sp. Acute
					Immobilisation Test)
Decamethylcyclopentasiloxan	EC50		48 h	Daphnia magna	OECD Guideline 202
e					(Daphnia sp. Acute
541-02-6					Immobilisation Test)

# Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Octamethylcyclotetrasiloxane	NOEC	7.9 µg/l	21 d	Daphnia magna	EPA OTS 797.1330
556-67-2					(Daphnid Chronic Toxicity
					Test)
Decamethylcyclopentasiloxan	NOEC		21 d	Daphnia magna	OECD 211 (Daphnia
e					magna, Reproduction Test)
541-02-6					
Dodecamethylcyclohexasiloxa	NOEC			Daphnia magna	OECD 211 (Daphnia
ne					magna, Reproduction Test)
540-97-6					

### Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Tetraethyl silicate	NOEC	22 mg/l	72 h	Pseudokirchneriella subcapitata	
78-10-4					Growth Inhibition Test)
Tetraethyl silicate	EC50	> 22 mg/l	72 h	Pseudokirchneriella subcapitata	, U
78-10-4					Growth Inhibition Test)
Octamethylcyclotetrasiloxane	EC50		96 h	Selenastrum capricornutum	EPA OTS 797.1050 (Algal
556-67-2				(new name: Pseudokirchneriella subcapitata)	Toxicity, Tiers I and II)
Octamethylcyclotetrasiloxane	NOEC	< 0,022 mg/l	96 h	Selenastrum capricornutum	EPA OTS 797.1050 (Algal
556-67-2				(new name: Pseudokirchneriella subcapitata)	Toxicity, Tiers I and II)
Hexamethyldisilizane	NOEC	2,7 mg/l	72 h		OECD Guideline 201 (Alga,
999-97-3				name: Desmodesmus	Growth Inhibition Test)
				subspicatus)	
Hexamethyldisilizane	EC50	19 mg/l	72 h	1 `	OECD Guideline 201 (Alga,
999-97-3				name: Desmodesmus	Growth Inhibition Test)
				subspicatus)	
Decamethylcyclopentasiloxan	NOEC		96 h	Selenastrum capricornutum	OECD Guideline 201 (Alga,
e 541-02-6				(new name: Pseudokirchneriella subcapitata)	Growth Inhibition Test)
Decamethylcyclopentasiloxan	EC50		96 h	Selenastrum capricornutum	OECD Guideline 201 (Alga,
e				(new name: Pseudokirchneriella	Growth Inhibition Test)
541-02-6				subcapitata)	
Dodecamethylcyclohexasiloxa	NOEC			Pseudokirchneriella subcapitata	
ne					Growth Inhibition Test)
540-97-6					
Dodecamethylcyclohexasiloxa	EC50			Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga,
ne					Growth Inhibition Test)
540-97-6					

## Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Tetraethyl silicate	EC50	> 100 mg/l	3 h	activated sludge of a	OECD Guideline 209
78-10-4				predominantly domestic sewage	(Activated Sludge,
					Respiration Inhibition Test)
Octamethylcyclotetrasiloxane	EC50		3 h	activated sludge	ISO 8192 (Test for
556-67-2					Inhibition of Oxygen
					Consumption by Activated
					Sludge)
Decamethylcyclopentasiloxan	EC0	> 10.000 mg/l	30 min	Pseudomonas putida	DIN 38412, part 27
e					(Bacterial oxygen
541-02-6					consumption test)

# 12.2. Persistence and degradability

The product is not biodegradable.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Silane, dimethoxydimethyl- 1112-39-6	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)
Tetraethyl silicate 78-10-4	readily biodegradable	aerobic	98 %	28 d	OECD Guideline 301 A (old version) (Ready Biodegradabiltiy: Modified AFNOR Test)
Octamethylcyclotetrasiloxane 556-67-2	not readily biodegradable.	aerobic	3,7 %	29 d	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)
Hexamethyldisilizane 999-97-3	not readily biodegradable.	no data	15,3 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Decamethylcyclopentasiloxan e 541-02-6	not readily biodegradable.	aerobic	0,14 %	28 d	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)
Dodecamethylcyclohexasiloxa ne 540-97-6	not readily biodegradable.	aerobic	4,47 %	28 d	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)

# 12.3. Bioaccumulative potential

No data available.

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
Octamethylcyclotetrasiloxane 556-67-2	12.400	28 d		Pimephales promelas	EPA OTS 797.1520 (Fish Bioconcentration Test-Rainbow Trout)
Decamethylcyclopentasiloxan e 541-02-6	7.060	35 d		Pimephales promelas	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
Dodecamethylcyclohexasiloxa ne 540-97-6	1.160	49 d		Pimephales promelas	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

# 12.4. Mobility in soil

Cured adhesives are immobile.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Silane, dimethoxydimethyl- 1112-39-6	2		EU Method A.8 (Partition Coefficient)
Tetraethyl silicate 78-10-4	0,04		QSAR (Quantitative Structure Activity Relationship)
Octamethylcyclotetrasiloxane 556-67-2	6,488	25,1 °C	OECD Guideline 123 (Partition Coefficient (1-Octanol / Water), Slow- Stirring Method)
Decamethylcyclopentasiloxan e 541-02-6	8,023	25,3 °C	OECD Guideline 123 (Partition Coefficient (1-Octanol / Water), Slow-Stirring Method)
Dodecamethylcyclohexasiloxa ne 540-97-6	8,87	23,6 °C	not specified

## 12.5. Results of PBT and vPvB assessment

Hazardous substances	PBT / vPvB
CAS-No.	
Tetraethyl silicate	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not
78-10-4	be conducted for inorganic substances.
Octamethylcyclotetrasiloxane	Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
556-67-2	Bioaccumulative (vPvB) criteria.
Hexamethyldisilizane	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
999-97-3	Bioaccumulative (vPvB) criteria.
Decamethylcyclopentasiloxane	very Persistent and very Bioaccumulative (vPvB)
541-02-6	
Dodecamethylcyclohexasiloxane	Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
540-97-6	Bioaccumulative (vPvB) criteria.

### 12.6. Other adverse effects

No data available.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Collection and delivery to recycling enterprise or other registered elimination institution.

### Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

#### Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

# **SECTION 14: Transport information**

#### 14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content (2010/75/EC) < 5 %

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

### National regulations/information (Germany):

WGK: WGK = 2, significantly water endangering mixture. Classification according to the mixture rules in German AwSV regulation annex 1, number 5.2 from 18. April 2017.

Storage class according to TRGS 510: 1

### **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H361f Suspected of damaging fertility.

H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

#### **Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

### Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.