



Safety Data Sheet according to GB/T 16483-2008

Page 1 of 8 .

LOCTITE 406 INSTANT ADHESIVE known as LOCTITE 406
INSTANT ADH. 1 kG

SDS No. : 153530

V001.7

Revision: 12.06.2017

printing date: 25.01.2019

1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE 406 INSTANT ADHESIVE known as LOCTITE 406 INSTANT ADH. 1 kG

Intended use: Cyanoacrylate

Company name:

Henkel (China) Investment Co. Ltd.
No.928 Zhangheng Rd.
201203 Pudong, Shanghai, P.R. China

China

Phone: +86-21-2891 8000

Fax-no.: +86-21-2891 5137

Revision date: 12.06.2017

Emergency information: Emergency telephone: +86 532 8388 9090 (24h).

2. Hazards identification

Classification of the substance or mixture according to GB 13690-2009 (General rule for classification and hazard communication of chemicals):

<u>Hazard Class</u>	<u>Hazard Category</u>	<u>Target organ</u>
Flammable liquids	Category 4	
Skin corrosion/irritation	Category 2	
Serious eye damage/eye irritation	Category 2A	
Specific target organ toxicity - single exposure	Category 3	respiratory tract irritation
Acute hazards to the aquatic environment	Category 3	

Label elements according to GB 15258-2009 (General rules for preparation of precautionary label for chemicals):

Hazard pictogram:



Signal word:

Warning

Hazard statement:	H227 Combustible liquid. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H402 Harmful to aquatic life.
Prevention:	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves, eye protection, and face protection.
Response:	P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P370+P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
Storage:	P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

3. Composition / information on ingredients

General description: Mixture
Declaration of the ingredients according to GB 13690-2009:

Hazard component CAS-No.	Content	GHS Classification
Ethyl 2-cyanoacrylate 7085-85-0	60- 100 %	Flammable liquids 4 H227 Skin corrosion/irritation 2 H315 Serious eye damage/eye irritation 2A H319 Specific target organ toxicity - single exposure 3 H335

Only hazardous ingredients for which a classification according to GB 13690-2009 is already available are displayed in this table. For full text of the Hazard statements see section 16 "Other information".

4. First aid measures

Skin contact:	Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such as a spoon, preferably after soaking in warm soapy water. Cyanoacrylates give off heat on solidification. In rare cases a large drop will generate enough heat to cause a burn. Burns should be treated normally after the adhesive has been removed from the skin. If lips are accidentally stuck together apply warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action.
Eye contact:	If the eye is bonded closed, release eyelashes with warm water by covering with wet pad. Cyanoacrylate will bond to eye protein and will cause periods of weeping which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Do not force eye open. Medical advice should be sought in case solid particles of cyanoacrylate trapped behind the eyelid cause any abrasive damage.
Inhalation:	Move to fresh air, consult doctor if complaint persists.
Ingestion:	Ensure that breathing passages are not obstructed. The product will polymerise immediately in the mouth making it almost impossible to swallow. Saliva will slowly separate the solidified product from the mouth (several hours).

5. Fire fighting measures

Extinguishing media:	Foam, extinguishing powder, carbon dioxide. Fine water spray
Notice and measures for firing fighting:	In the event of a fire, carbon monoxide (CO), carbon dioxide (CO ₂) and nitrogen oxides (NO _x) can be released. Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

6. Accidental release measures

Emergency measures:	Ensure adequate ventilation. Do not let product enter drains.
Clean-up methods:	Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste.
Precautions measures to prevent secondary hazards:	No information.

7. Handling and storage


Notice for handling:	Ventilation (low level) is recommended when using large volumes
Notice for storage:	Use of dispensing equipment is recommended to minimise the risk of skin or eye contact For optimum shelf life store in original containers under refrigerated conditions at 2 - 8°C (35.6 - 46.4 °F) Store in original container at temperatures 0 - 10 °C.
Temp. limits storage/ transportation:	Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

8. Exposure controls / personal protection

Hazardous components	GBZ 2.1-2007	ACGIH	NIOSH	OSHA
Hydroquinone	1 mg/m ³ PC-TWA 2 mg/m ³ PC-STEL	1 mg/m ³ TWA		none

- Engineering controls:** Use positive down-draft exhaust ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.
- Respiratory protection:** Ensure adequate ventilation.
- Eye protection:** Wear protective glasses.
- Body protection:** Use nitrile gloves and aprons as necessary to prevent contact. Do not use PVC, nylon or cotton.
- Hand protection:** In circumstances where there is a potential for prolonged or repeated skin contact, the use of disposable gloves (polyethylene, natural rubber or equivalent ester-resistant material) is recommended.
The use of chemical resistant gloves such as Nitrile is recommended.

Pictograms for recommended PPE:



9. Physical and chemical properties

Physical state:	liquid	Appearance:	colourless liquid
pH:	Not applicable	Melting point:	Not available.
Boiling point:	> 149 °C (> 300.2 °F)	Density:	1.1000 g/cm ³
Flash point:	80.0 - 93 °C (176 - 199.4 °F)	Ignition temperature:	Not available.
Solubility in water	Not available.	Viscosity:	100 mPa.s

10. Stability and reactivity

- Stability:** Stable under recommended storage conditions.
- Conditions to avoid:** Stable under normal conditions of storage and use.
- Incompatible products:** Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.
- Decomposition products:** None
- Hazardous polymerization:** Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

11. Toxicological information**General toxicological information:**

No laboratory animal data available.

Other remarks:

Not available.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	LD50 LD50	> 5,000 mg/kg > 2,000 mg/kg	oral dermal		rat rabbit	OECD Guideline 401 (Acute Oral Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	slightly irritating	24 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	irritating	72 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	not sensitising		guinea pig	not specified

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	negative negative negative	bacterial reverse mutation assay (e.g Ames test) mammalian cell gene mutation assay in vitro mammalian chromosome aberration test	with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)

12. Ecological information**General ecological information:**Biological and Chemical Oxygen Demands (BOD and COD) are insignificant.
Do not empty into drains / surface water / ground water.**Ecotoxicity:**

No data available.

Other adverse effects:

Do not empty into drains, soil or bodies of water.

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Ethyl 2-cyanoacrylate 7085-85-0		aerobic	57 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Ethyl 2-cyanoacrylate 7085-85-0	0.776				22 °C	EU Method A.8 (Partition Coefficient)

13. Disposal considerations

Product disposal:

If the waste is classified as hazardous waste according to GB 5085.7-2007 (Identification standards for hazardous wastes, General Specifications). Dispose of as hazardous waste in compliance with "Regulation on the Safety Management of Hazardous Chemicals", "Law of the People's Republic of China on the prevention and control of Environmental Pollution by Solid Waste", "National Catalogue of Hazardous Waste".

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated. Disposal must be made according to official regulations.

14. Transport information

Road transport ADR:

Not dangerous goods

Railroad transport RID:

Not dangerous goods

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Class:	9
Packing group:	III
Packaging instructions (passenger):	964
Packaging instructions (cargo):	964
UN no.:	3334
Label:	9
Proper shipping name:	Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)
Additional Information:	Primary packs containing less than 500ml are unregulated by this mode of transport and may be shipped unrestricted.

Notice For Transportation:

Transport according to local and national regulations. Ensure containers will not leak, collapse, or being damaged when transported. DO NOT transport with incompatible materials. Transportation vehicle should be equipped with right fire-fighting equipment in case of emergency. Avoid solarization, drenched and high temperature when transported.

15. Regulatory information

The following laws and regulations lay down provisions in terms of chemicals safety use, storage, transportation, loading/unloading, classification as well as symbol.

“Law of the People's Republic of China on Work Safety” (Adopted by the 28th meeting of 9th NPC standing committee on 29th June 2002, revised by 10th meeting of 12nd NPC standing committee on 31st Aug 2014).

“Law of the People's Republic of China on the Prevention and Treatment of Occupational Diseases” (Adopted by the 24th meeting of 9th NPC standing committee on 27th October 2001, revised by 21st meeting of 12nd NPC standing committee on 2nd Jul 2016).

“Law of the People's Republic of China on environmental protection” (Adopted by 11st meeting of 7th NPC standing committee on 26th December 1989, revised by 8th meeting of 12nd NPC standing committee on 24th Apr 2014).

“Regulation on the Safety Management of Hazardous Chemicals” (Adopted by 144th State Council executive meeting on 16th February 2011).

“Regulations on License to Work Safety” (Adopted by 54th State Council executive meeting on 29th July 2014).

China Inventory of Existing Chemicals:

All components are listed or are exempt from Inventory of Existing Chemical Substances in China.

16. Other information

Issue date:

25.01.2019

Issue department:

Lisa Zhang, Senior Product Safety & Regulatory Affairs Specialist.

Disclaimer:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties. The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Others:

The full text of all abbreviations indicated by codes in this safety data sheet section 3 are as follows:

H227 Combustible liquid.
H315 Causes skin irritation.
H319 Causes serious eye irritation.