

Safety Data Sheet according to GB/T 16483-2008

Page 1 of 9.

LOCTITE 569 known as 569 THREAD SEALANT 50ML EN/JP/C

SDS No.: 150775 V001.5

Revision: 04.01.2018 printing date: 19.02.2019

1. Identification of the substance/preparation and of the company/undertaking

LOCTITE 569 known as 569 THREAD SEALANT 50ML EN/JP/C **Product name:**

Anaerobic Sealant **Intended use:**

Company name:

Henkel (China) Investment Co. Ltd.

No.928 Zhangheng Rd.

201203 Pudong, Shanghai, P.R. China

China

Phone: +86-21-2891 8000 +86-21-2891 5137 Fax-no.:

04.01.2018 **Revision date:**

2. Hazards identification

Classification of the substance or mixture according to GB 13690-2009 (General rule for classification and hazard communication of chemicals):

Hazard Class Hazard Category Target organ

Serious eye damage/eye irritation Category 2A Specific target organ toxicity -

Category 3

respiratory tract irritation

single exposure

Acute hazards to the aquatic Category 3 environment Chronic hazards to the aquatic Category 3

environment

Label elements according to GB 15258-2009 (General rules for preparation of precautionary label for chemicals):

Hazard pictogram:

Signal word: Warning

Page 2 of 9.

SDS No.: 150775 V001.5

LOCTITE 569 known as 569 THREAD SEALANT 50ML

EN/JP/C

Hazard statement: H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Prevention: P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment. P280 Wear eye protection/face protection.

Response: P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

Storage: P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal: P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product characteristics at time of

disposal.

Page 3 of 9.

SDS No.: 150775 V001.5

LOCTITE 569 known as 569 THREAD SEALANT 50ML

EN/JP/C

3. Composition / information on ingredients

General description: Mixture

Declaration of the ingredients according to GB 13690-2009:

Hazard component CAS-No.	Content	GHS Classification
Cumene hydroperoxide	1- < 10 %	Flammable liquids 4
80-15-9		H227
		Organic peroxides E
		H242
		Acute toxicity 4; Oral
		H302
		Acute toxicity 3; Inhalation
		H331
		Acute toxicity 4; Dermal
		H312
		Skin corrosion/irritation 1B H314
		Specific target organ toxicity - repeated exposure 2 H373
		Acute hazards to the aquatic environment 2 H401
		Chronic hazards to the aquatic environment 2 H411
1,4-Naphthalenedione	< 0.1 %	Acute toxicity 3; Oral
130-15-4	,	H301
		Acute toxicity 1; Inhalation
		H330
		Skin corrosion/irritation 2; Dermal H315
		Serious eye damage/eye irritation 2A H319
		Skin sensitizer 1; Dermal
		H317
		Specific target organ toxicity - single exposure 3; Inhalation
		H335
		Acute hazards to the aquatic environment 1 H400
		Chronic hazards to the aquatic environment 1 H410

Only hazardous ingredients for which a classification according to GB 13690-2009 is already available are displayed in this table. For full text of the Hazard statements see section 16 "Other information".

4. First aid measures

Skin contact: Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact: Rinse immediately with plenty of running water (for 10 minutes), seek medical attention

from a specialist.

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Ingestion: Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

5. Fire fighting measures

Extinguishing media: Carbon dioxide, foam, powder

Page 4 of 9.

SDS No.: 150775

V001.5

LOCTITE 569 known as 569 THREAD SEALANT 50ML

EN/JP/C

Notice and measures for firing

fighting:

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides

(NOx) can be released.

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

6. Accidental release measures

Emergency measures: Avoid skin and eye contact.

Do not let product enter drains. Ensure adequate ventilation.

Clean-up methods: For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for

disposal.

7. Handling and storage

Notice for handling: Use only in well-ventilated areas.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Avoid skin and eye contact. See advice in section 8

Notice for storage: Refer to Technical Data Sheet

Temp. limits storage/ transportation:

Engineering controls:

Respiratory protection:

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep

container tightly closed until ready for use.

8. Exposure controls / personal protection

Hazardous components	GBZ 2.1-2007	ACGIH	NIOSH	OSHA
Cumene hydroperoxide	none	none		none
1,4-Naphthalenedione	none	none		none

limits.

Eye protection: Wear protective glasses.

Body protection: Wear suitable protective clothing.

Hand protection: The use of chemical resistant gloves such as Nitrile is recommended.

Please note that in practice the working life of chemical resistant gloves may be


considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed

Provide adequate local exhaust ventilation to maintain worker exposure below exposure

then the gloves should be replaced.

Use only in well-ventilated areas.

Pictograms for recommended PPE:



Page 5 of 9.

SDS No.: 150775 V001.5

LOCTITE 569 known as 569 THREAD SEALANT 50ML

EN/JP/C

9. Physical and chemical properties

Physical state: liquid Appearance: brown liquid

Not applicable Melting point: Not available. pH: Density: Boiling point: > 150 °C (> 302 °F) 1.049 g/cm3 > 93.3 °C (> 199.94 °F) Flash point: Ignition temperature: Not available. Solubility in water Viscosity: 300 - 500 mPa.s Slight

10. Stability and reactivity

Conditions to avoid: No decomposition if used according to specifications.

Incompatible products: Reacts with strong oxidants.

Decomposition products: Irritating organic vapours.

carbon oxides. Sulphur oxides nitrogen oxides

Hazardous polymerization: None under normal processing. Polymerization may occur at elevated temperature or in

the presence of incompatible materials.

11. Toxicological information

Oral toxicity:

Acute toxicity estimate (ATE) : > 5,000 mg/kg

Method: Calculation method

Inhalative toxicity:

Acute toxicity estimate (ATE) : > 40 mg/l

Exposure time: 4 h Test atmosphere: Vapor. Method: Calculation method

Dermal toxicity:

Acute toxicity estimate (ATE) : > 5,000 mg/kg

Method: Calculation method

Other remarks:

Not available.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Cumene hydroperoxide	LD50	550 mg/kg	oral		rat	not specified
80-15-9	LD50	1,200 - 1,520				not specified
		mg/kg	dermal			
1,4-Naphthalenedione 130-15-4	LD50	190 mg/kg	oral		rat	not specified

Page 6 of 9.

SDS No.: 150775 V001.5

LOCTITE 569 known as 569 THREAD SEALANT 50ML EN/JP/C

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	corrosive		rabbit	Draize Test

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	negative	dermal		mouse	not specified

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Cumene hydroperoxide 80-15-9		inhalation: aerosol	6 h/d5 d/w	rat	not specified

12. Ecological information

General ecological information:

Cured Loctite products are typical polymers and do not pose any immediate environmental hazards. Do not empty into drains / surface water / ground water.

Ecotoxicity:

No data available.

Other adverse effects:

Do not empty into drains, soil or bodies of water.

Toxicity:

Hazardous components	Value	Value	Acute	Exposure	Species	Method
CAS-No.	type		Toxicity	time		
			Study			
Cumene hydroperoxide	LC50	3.9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline
80-15-9						203 (Fish, Acute
	[Į			Toxicity Test)
Cumene hydroperoxide 80-15-9	EC 50	7 mg/l	Daphnia	24 h	Water flea (Daphnia magna)	
Cumene hydroperoxide	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
80-15-9			_			202 (Daphnia sp.
						Acute
						Immobilisation
						Test)
Cumene hydroperoxide	ErC50	3.1 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline
80-15-9						201 (Alga, Growth
						Inhibition Test)
Cumene hydroperoxide	EC10	70 mg/l	Bacteria	30 min		not specified
80-15-9						
1,4-Naphthalenedione	EC50	0.011 mg/l	Algae	72 h	Dunaliella bioculata	OECD Guideline
130-15-4						201 (Alga, Growth
						Inhibition Test)

Page 7 of 9.

SDS No.: 150775 V001.5

LOCTITE 569 known as 569 THREAD SEALANT 50ML

EN/JP/C

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Cumene hydroperoxide 80-15-9		no data	0 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
1,4-Naphthalenedione 130-15-4		no data	0 - 60 %	OECD 301 A - F

Bioaccumulative potential / Mobility in soil:

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			
Cumene hydroperoxide		9.1		calculation		OECD Guideline 305
80-15-9						(Bioconcentration: Flow-
						through Fish Test)
Cumene hydroperoxide 80-15-9	2.16					not specified
1,4-Naphthalenedione 130-15-4	1.71					not specified

13. Disposal considerations

Product disposal: Collection and delivery to recycling enterprise or other registered elimination institution.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

14. Transport information

General information:

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

Notice For Transportation: Transport according to local and national regulations. Ensure

containers will not leak, collapse, or being damaged when transported. DO NOT transport with incompatible materials. Transportation vehicle should be equipped with right fire-fighting equipment in case of emergency. Avoid solarization, drenched and high temperature when

transported.

Page 8 of 9.

SDS No.: 150775 V001.5

LOCTITE 569 known as 569 THREAD SEALANT 50ML

EN/JP/C

15. Regulatory information

The following laws and regulations lay down provisions in terms of chemicals safety use, storage, transportation, loading/unloading, classification as well as symbol.

"Law of the People's Republic of China on Work Safety" (Adopted by the 28th meeting of 9th NPC standing committee on 29th June 2002, revised by 10th meeting of 12nd NPC standing committee on 31st Aug 2014).

"Law of the People's Republic of China on the Prevention and Treatment of Occupational Diseases" (Adopted by the 24th meeting of 9th NPC standing committee on 27th October 2001, revised by 21st meeting of 12nd NPC standing committee on 2nd Jul 2016).

"Law of the People's Republic of China on environmental protection" (Adopted by 11st meeting of 7th NPC standing committee on 26th December 1989, revised by 8th meeting of 12nd NPC standing committee on 24th Apr 2014).

"Regulation on the Safety Management of Hazardous Chemicals" (Adopted by 32nd State Council executive meeting on 4th December 2013).

"Regulations on License to Work Safety" (Adopted by 54th State Council executive meeting on 29th July 2014).

China Inventory of Existing Chemicals:

All components are listed or are exempt from Inventory of Existing Chemical Substances in China

16. Other information

Issue date:

Issue department:

Disclaimer:

19.02.2019

Dayong Tian, Product Safety & Regulatory Affairs Specialist for Greater China

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties. The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Others:

The full text of all abbreviations indicated by codes in this safety data sheet section 3 are as follows:

H227 Combustible liquid.

H242 Heating may cause a fire.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H401 Toxic to aquatic life.

SDS No.: 150775 V001.5

LOCTITE 569 known as 569 THREAD SEALANT 50ML EN/JP/C

Page 9 of 9.